

VELVET C DESIGN

OutFit / Serve-over counters


Serve-over



BEST ENERGY CLASS*



Product Categories



Cheese

Dairy
products

Delicatessen

Gastronomy

Meat

Chicken

Technical Features



High
efficiency
fans

LED lighting

Off-cycle
defrost

Remote
condensing
unit

Ventilated

VELVET C DESIGN

OutFit / Serve-over counters

Serve-over

Certification and Patents



Eurovent



TechnoKleen



Epta
Adamant

Product Range


VELVET C DESIGN									
Length-Lunghezza Longueur-Länge-Longitud mm	937	1250	1875	2500	3125	3750	MAA 90°	MAA 45°	MAC 45°
RDB	•	•	•	•	•	•			
RDA	•	•	•	•		•	•	•	
WO	•	•	•	•		•		•	•
RDBP	•	•	•	•		•	•	•	•
RCB	•	•	•	•	•	•	•	•	•
LS	•	•	•	•	•	•	•	•	•
Display area Superficie di esposizione Warenpräsentationsfläche Surface d'exposition Superficie expositiva m2/ml	0.75								
Loading area Superficie di appoggio Nutzfläche Surface de chargement Superficie de apoyo m2/ml	1.01								
End thickness Spessore spalla Stärke der Seitenwand Épaisseur de cheue joue Espesor lateral mm	35.00								

VELVET C DESIGN


OutFit / Serve-over counters

Serve-over


Cross Sections




Design RDBP



Design LS-U



Design RDB







Design WO

VELVET C DESIGN

OutFit / Serve-over counters

Serve-over



*The information on the energy class (according to EU regulations 2019/2018 and EU 2019/2024) reported here refers to standard models and precise product configurations and set-ups. The site is based on the information available at the time of publication. As the energy class depends on the specific product configuration, despite the efforts made to ensure the greatest possible accuracy, the real data can differ significantly from the data declared here. For further information, we invite you to consult the European Product Database for Energy Labelling (EPREL) or to contact our Sales Office.